

FIG. 1

Byte 0: LANGUAGE NUMBER, APPLICATION CODE

-bit 6-4 = LANGUAGE NUMBER


000 Language-independent text, or only one language is provided.

001 Main language if various languages are recorded.

-bit 3-0 = APPLICATION CODE

0000 Text Packet for 2-line and 21-line displays, based on a 40-character per line font.
1000 As "0000", but also for 1-line displays.

FIG. 3



F16.2

Col/Row		1 Line Display Control codes
11 15 19 1A 1B	S P H0 H1 H2	Start code Pause code Scroll, default speed Scroll, speed 2 Scroll, speed 3
1C	Н3	Scroll,: speed 4

FIG.4

	0x	1 ₁ x	2x	3x	l 4x	 5x	l fix	 7x	 8x	Q _Y	امد	l _R ,	ار	امر	ادر	Fx
x0				0	@	P	`	P		3.	\ \frac{1}{1}	٥٠	<u>د ۸</u>	101		1.
x 1	Ť	_	!	1	A	a	а	q	-							
x2								٦	-							
x 3								s	_							
x 4								t	-							
x5	DES		-					u								
x 6	0 0		_					٧								
x7	CONTROL CODES		•					w	_		8 8					
<u>x8</u>	_		-		0			x			7	֡֝֝֝֝֟֝֝֝֝֝֝֝֝֝֝֝֝֝֝֝֝֝֟֝				
x9	_			1	LHAKALIEKS		у	у			SPECIAL CUABACTERS	\ \ \ \ \ \ \				
ΧA	_			404	AKA		T	Z	CODEC		-	<u>.</u>				
хВ	_			5	5		T	{			FCIA	<u> </u>				
χC	-	I		OTUCD	ITEN		T	1	CONTROL		ď	5				
хD	_	\prod		ċ	>		T	}	ב	1						
хE	-	T					Ţ	~								
хF		T						丁	ı							

FIG.9

TAPE FRAME (N):

8 bytes Sysinfo header	SIO			
b bytes systilo fleuder	SI ₇			
8 bytes packet header	SI8	Packet 1		
bytes paoner nedder	SI ₁₅	1 deket 1		
40 bytes Coded text line	SI ₁₆	Packet 1		
40 bytes coded text time	SI55			
8 bytes packet header	SI56	Packet 2		
o bytes pucket nedder	S163	Tucket 2		
40 bytes of coded text line	SI ₆ 4	Packet 2		
40 bytes of coded text time	SI <u>103</u>			
8 bytes packet header	SI ₁₀₄	Packet 3		
o bytes packet neader	SI ₁₁₁			
16 bytes of bytes of coded	SI ₁₁₂	Packet 3		
text line	SI ₁₂₇	Ideket 3		

TAPE FRAME (N+1):

		•		
8 bytes Sysinfo header	SIO			
o bytes sysimo neddei	SI7			
24 bytes of coded text line	SI8	Packet 3		
24 bytes of coded text line	SI31	- ucket		
9 hytes packet header	SI32	Packet 4		
8 bytes packet header	SI 39	rucket 4		
40 bytes of coded text line	SI40	Packet 4		
40 bytes of coded text time	SI79			
8 bytes packet header	2180	Packet 5		
o bytes packet neader	SI87	I donet o		
40 bytes of coded text line	SIgg	l Packet 5		
To bytes of coded text line	SI 127			

FIG.5




FIG. 6




FIG. 7

ABC HIJKL M 100

F16.8a

TOON ERDL

F 16.8b

32 33 34 35 36 37 38 39 40 31 30 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 K L M N - S M I A - - - - - H 13 12 z 170 9 10 T D ∞ - 1 100 ဖ - 1 ന പ 4 œ 3 ⋖ 0

4 Σ

F16.8c

22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 R S - - - I U V - - - W - - - X Y - Z 9 10 11 12 13 14 15 16 17 18 19 20 21 9 1 ؎ 0 Z Σ Ŧ ∞ Ġ 9 w 345 ABCD ~ 全

女 8 じ D E F G H I 丿 K ABCOULOTHUX JX 女 色 じ D 生 上 り 井 1 1 k **ABCOMFOHIA** ABOOMFOE, **ABCOMFOF** A B C D E F S H **ABCOHF**6 A B C D H L **ABC** t11 t12 A t13 B t1% C けははおけばはははは